

MOWERS

Europe



INTRODUCTION B4502510-EN (07-23)

INTRODUCTION

OUR MISSION

We empower operators to accomplish more, while working in the toughest conditions and tightest situations. When our customers have the will, we provide the way.

BOBCAT'S HISTORY

In 1958, Melroe Manufacturing Company introduced a compact front-end loader that evolved quickly into the M400, the world's first true skid steer loader. The company soon adopted what became the world-famous 'Bobcat' brand – and its success paved the way for the global compact equipment industry we know today.

▶ YEARS OF EXPERIENCE

Our Johnson Creek facility has been building tough and reliable mowers since 1972. That's more than 50 years of experience and know-how behind every mower that leaves the factory.



BOBCAT TODAY

Inspired by success in the North American market, we introduced our new line of mowers in Europe to help customers meet new challenges and expand their business backed by reliable and tough equipment.



B4502510-EN (07-23)

ENGINEERED TO KEEP YOU ON TOP OF YOUR GAME

SIMPLICITY, PRODUCTIVITY AND DURABILITY

Change the way you work with Bobcat's mowers: intuitive machines that combine ease of use with agility and outstanding cutting quality. With multiple configurations, a robust build and easy servicing, these mowers give you the power to deliver perfect results for years to come.







UNBEATABLE PRODUCTIVITY

Bobcat Mowers empower you to get more done in less time thanks to superior mowing speed, outstanding maneuverability, and agility on the job site.



A PREMIUM CUT

Impress your clients thanks to the impeccable cutting quality of our mowers. With innovative deck designs and easily adjustable cutting height, you get perfect results every time.



DEPENDABLE & TOUGH

With over 50 years of experience in designing and manufacturing mowers, Bobcat has all the know-how to make sure that you are getting a durable, dependable machine.



THE SIMPLE JOY OF WORKING

The smooth controls, comfort, agility, and fast mowing speeds all combine for a truly rewarding and satisfying experience that will bring a smile to your face.

PERFORMANCE





▶ GET STARTED IN MINUTES

Thanks to a brilliantly simple and intuitive control scheme, you don't need to spend time getting familiar with the machine - you can go straight to being productive. The smooth operation and zero-turn movement mean that you will zip around the lawn in minutes.

EXCELLENT MANEUVERABILITY

With zero-turn movement and responsive, sensitive controls that feel intuitive to use, you move around the lawn with precision and confidence. You avoid obstacles like trees or poles easily - getting every job done with finesse.





A STABLE RIDE

Thanks to the low center of gravity and wide wheelbase, our mowers provide unbeatable stability that immediately inspires confidence at any speed and any turn. With a number of safety features added in, these machines quickly become your trusted partner for achieving outstanding results.

▶ FIND THE PERFECT CONFIGURATION

With a comprehensive line-up of ride-on, stand-on and walk-behind mowers in entry-level as well as professional models, you're sure to find the machine that works for you and your budget. You can further customise your mower with a wide selection of cutting decks or mulching and collection systems, available on all our models.



A RIDE LIKE NO OTHER









EASY ACCESS & INTUITIVE CONTROLS

Bobcat Mowers provide easy access to the operator's position, so you can start working in seconds. With the comfortable seat with high backrest, well-placed padding for extra comfort and protection of your knees, and ergonomic controls, rest assured: these machines provide a ride like no other.



▶ INTUITIVE CONTROL PANEL



Enjoy the intuitiveness and comfort provided by the control panel with well-placed ergonomic controls, which enables you to get in sync with your machine in almost no time.

▶ ROBUST ANTI-SLIP PLATFORM



The Bobcat stand-on mowers are equipped with a robust anti-slip standing armrests and high back, so you can sit platform that can be lifted quickly and easily, so you have more control over your machine in tight spaces.

▶ COMFORTABLE SEAT



The seat is equipped with adjustable comfortably with less fatigue.



BUILT TO LAST

▶ TOUGH PARTNER

Bobcat mowers are based on a durable, robust and smart design, which limits wear and tear on all components while making regular service easy to perform. This prolongs the machine's longevity and protects the value of your investment.



▶ BOBCAT PPE

With Bobcat Personal Protective Equipment, you can rest assured that you're getting the best protection for your eyes, head, and body. Our safety glasses are made with impactresistant lenses that keep debris and dust out of your eyes. Our vests, jackets and pants are made with durable materials to withstand tough work environments and are designed to keep you comfortable while you work.

STANDARD WARRANTY

Bobcat develops every machine to the highest standards of quality and durability. According to your needs, you can benefit from coverage for up to 5 years.

HARSHEST CONDITIONS.

B4502510-EN (07-23)

THERE'S NO TIME

FOR DOWNTIME.

DAY AFTER DAY.

STAND UP TO THE







▶ PROTECTION PLUS EXTENDED WARRANTY

Enjoy total peace of mind with a Protection Plus® extended warranty. Providing the same level of protection as the standard warranty, Protection Plus also reflects different customer needs and expectations by offering a choice of durations and annual operating hours. Configure the warranty coverage that works for you with options up to 5 years. And Protection Plus is transferrable – so it will likely increase your machine's resale value.



▶ BOBCARE PM

A long-running machine starts with proper planned maintenance, which also helps protect against repair costs and unplanned failures when you're counting on your machine to work.

- Avoid risk by preventing major repairs and complete failures.
- · Accomplish more by reducing downtime and increasing your productivity and profitability.



CHOOSE YOUR ANIMAL





STAND-ON

▶ PERFECT AGILITY

The Bobcat Stand-on Mowers are perfectly agile machines that deliver the best cutting results even on heavily landscaped grounds. They allow you to easily hop off and back on when you need to clear obstacles from your path or open fences.

WALK-BEHIND

TRANSFORMING THE WAY YOU WORK

These compact yet powerful machines are the best solution for those smaller jobs on an uneven terrain that require maximum agility. With exceptional maneuverability, great visibility, and perfect cut quality, they boost your productivity and allow you to work in places others cannot.





WALK-BEHIND MOWERS

CUTTING DECK WIDTH	122 cm		132 cm		
ENGINE					
Model	Kaw FS541V		Kaw FS600V		
Engine power	11.1 kW / 15 HP		13.7 kW / 18.5 HP		
Displacement		603 cm ³			
Fuel capacity		18.9			
Air filter		Dual element			
ELECTRICAL					
Charging system		15 A			
Clutch		467 N			
DECK					
Mower deck	TufDeck Cutting System				
Width	122 cm / 48"		132 cm / 52"		
Adjustable anti-scalp rollers		3			
Cutting height	38 - 114 mm				
Blade tip speed	74.7 m/s @ 3 550 engine rpm		82.8 m/s @ 3 550 engine rpm		
Discharge chute	Fle	xible molded polymer			
RAME					
ront and rear	1.5 - \times 2.5 -inch stee	l tubing; welded steel re	inforced frame		
Machine length		1 981 mm			
Nachine weight	357 kg		377 kg		
RANSMISSION					
уре	HG ZT-	2800 with Charge Pump	os		
Pump displacement		10 cm ³			
Oil capacity		3.8 I			
orward speed		10.5 km/h			
Reverse speed		4.8 km/h			
VHEELS					
Orive wheel size		20 × 8			
Front caster wheel size	11	× 6 semi-pneumatic			
Caster arm attachment		Welded to frame			



CU	TTING DECK WIDTH	122 cm	132 cm
A	Height	11	05 mm
3	Overall length	1 9	81 mm
C	Overall width (chute up)	1 227 mm	1 328 mm
C	Overall width (chute down)	1 577 mm	1 679 mm
0	Cutting height	38 -	114 mm
E	Wheelbase	11	68 mm
F	Cutting width	914 mm	1 321 mm
G	Blade length	413 mm	457 mm






Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors. Pictures of Bobcat units may show other than standard equipment.


STAND-ON ZERO-TURN MOWERS

SPECIFICATIONS ZS4000			
CUTTING DECK WIDTH	122 cm	132 cm	155 cm
ENGINE			
Model	Kaw FT651V	Kaw	FT730V
Engine power	14.9 kW / 20 HP	17.9 k	W / 24 HP
Displacement		726 cm ³	
Fuel capacity		24.6	
Air filter		Dual Element	
ELECTRICAL			
Charging system		15 A	
Clutch		889 N	
DECK			
Mower deck		AirFX Cutting System	
Leading edge		Adjustable, Front Lip Standard	
Width	122 cm / 48"	132 cm / 52"	155 cm / 61"
Adjustable anti-scalp rollers		4	7
Cutting height		38 - 124 mm	
Blade tip speed	84.3 m/s @ 3 550 engine rpm	81.5 m/s @ 3 550 engine rpm	85.4 m/s @ 3 550 engine rpm
Discharge chute		Flexible molded polymer	
FRAME			
Front and rear	1.5-	x 2.5-inch steel tubing; welded steel reinforced	frame
Machine length		1 625 mm	
Machine weight	435 kg	449 kg	466 kg
TRANSMISSION			
Туре		HG ZT-3400 hydrostatic transaxles	
Pump displacement		12 cm ³	
Oil capacity		3.8 I	
Forward speed		16.8 km/h	
Reverse speed		5.6 km/h	
WHEELS			
Drive wheel size	23 × 8.5-12	23 ×	10.5-12
Front caster wheel size		$13 \times 6.5 - 6$	
Caster arm attachment		Bolt-on	
OPERATOR PLATFORM			
Adjustment		Flip up and latch	
Rider pad		Removable for service	
Vibration isolation		Dampened	



CUTTING DECK WIDTH	122 cm	132 cm	155 cm
A Height		1 062 mm	
3 Overall length		1 626 mm	
Overall width (chute up)	1 229 mm	1 369 mm	1 575 mm
Overall width (chute down)	1 546 mm	1 686 mm	1 854 mm
Cutting height		38 - 124 mm	
Wheelbase	1 135 mm	1 265 mm	
F Cutting width	1 220 mm	1 330 mm	1 550 mm
G Blade length	410 mm	460 mm	530 mm





Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors. Pictures of Bobcat units may show other than standard equipment.

RIDE-ON ZERO-TURN MOWERS


SPECIFICATIONS		ZT3000			ZT3500	
CUTTING DECK WIDTH	122 cm	132 cm	155 cm	122 cm	132 cm	155 cm
ENGINE						
Model	Kaw FT651V			Kaw FT730V		
Engine power	14.9 kW / 20 HP			17.9 kW / 24 HP		
Displacement			726	cm ³		
Fuel capacity		14.3			29.5	
Air filter	Dual element			Dual element		
ELECTRICAL						
Charging system			15	5 A		
Clutch			55	6 N		
DECK						
Mower deck		TufDeck Cutting System	1	Tu	fDeck Pro Cutting Syste	em
Width	122 cm / 48"	132 cm / 52"	155 cm / 61"	122 cm / 48"	132 cm / 52"	155 cm / 61"
Adjustable anti-scalp rollers	;	3	7	;	3	7
Cutting height			38 - 1	24 mm		
Blade tip speed	73.6 m/s @ 3 550 engine rpm	81.5 m/s @ 3 550 engine rpm	85.4 m/s @ 3 550 engine rpm	73.6 m/s @ 3 550 engine rpm	81.5 m/s @ 3 550 engine rpm	85.4 m/s @ 3 550 engine rpm
Discharge chute			Flexible mol	ded polymer		
FRAME						
Front and rear		1.5- >	× 2.5-inch steel tubing;	welded steel reinforced	frame	
Machine length			1 930 mm			2 006 mm
Machine weight	343 kg	351 kg	370 kg	350 kg	357 kg	377 kg
TRANSMISSION						
Туре	HG Z	T-3100 hydrostatic trans	saxles	HG Z	Γ-3400 hydrostatic trans	saxles
Pump displacement		10 cm ³			12 cm ³	
Oil capacity			3.	8		
Forward speed		12.8 km/h			16 km/h	
Reverse speed			5.6 l	km/h		
WHEELS						
Drive wheel size		22 × 11-10			23 × 10.5-12	
Front caster wheel size			13 ×	6.5-6		
Caster arm			Welded	to frame		
SEAT						
Description	High back	x, EVC and spring suspe	nsion seat	High back, full mechanical suspension seat	High-Back, EVC and spring suspension seat	High back, full mechanical suspension seat
Fore-aft adjustment			Seat sli	de lever		


Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors. Pictures of Bobcat units may show other than standard equipment.



OUTTING DESK HUDTU						
CUTTING DECK WIDTH		122 cm	132 cm	155 cm		
A	Height		1 173 mm			
В	Overall Length		1 930 mm			
C	Overall Width (Chute Up)	1 241 mm	1 381 mm	1 600 mm		
C	Overall Width (Chute Down)	1 575 mm	1 734 mm	1 949 mm		
D	Cutting Height		38 - 124 mm			
E	Wheelbase		1 220 mm			
F	Cutting Width	1 220 mm	1 321 mm	1 550 mm		
G	Blade Length	413 mm	457 mm	533 mm		

CU	TTING DECK WIDTH	122 cm	132 cm	155 cm
A	Height (ROPS Up)		1 733 mm	
A	Height (ROPS Down)		1 190 mm	
В	Overall Length		1 930 mm	
C	Overall Width (Chute Up)	1 241 mm	1 381 mm	1 600 mm
C	Overall Width (Chute Down)	1 575 mm	1 734 mm	1 949 mm
D	Cutting Height		38 - 124 mm	
E	Wheelbase		1 220 mm	
F	Cutting Width	1 220 mm	1 321 mm	1 550 mm
G	Blade Length	413 mm	457 mm	533 mm







120 MACHINES / 150 ATTACHMENT FAMILIES / 1 TOUGH ANIMAL



SKID-STEER LOADERS



COMPACT TRACK LOADERS



COMPACT WHEEL LOADERS



FORKLIFTS



TELEHANDLERS



ROTARY TELEHANDLERS



LIGHT COMPACTION EQUIPMENT



COMPACT EXCAVATORS



ATTACHMENTS



SMALL ARTICULATED LOADERS



MINI TRACK LOADER



MOWERS




COMPACT TRACTORS

Bobcat







Doosan Bobcat EMEA, U Kodetky 1810, 263 12 Dobříš, Czech Republic